

E Series NV Uninterruptible Power System



Affordable Power Protection for Today's Business Environment

Introducing the E Series NV UPS

The E Series NV line interactive uninterruptible power system (UPS) from Eaton® provides affordable power protection for your personal computer and peripherals. While packed with valuable features such as modem protection and plentiful power receptacles, the compact size is ideal for limited office and home working spaces.

Product snapshot

Power Rating:	400, 600, 800, 1000, 1400, 2000 VA tower models
Voltage:	81 to 145Vac (low voltage) 162 to 290Vac (high voltage)
Frequency:	50/60 Hz (auto-sensing)
Technology:	Automatic Voltage Regulation



Features

- Automatic Voltage Regulation (AVR) stabilizes fluctuating power sources
- Microprocessor control design ensures high reliability
- Up to six receptacles, allowing easy equipment connection
- User replaceable batteries allow easy maintenance
- Start-on-battery provides portable power capability
- WINPOWER software monitors power conditions and gracefully shuts down computer applications prior to battery depletion
- Data surge protection protects phone, modem and internet connections
- Intuitive LED indicators display UPS status



Powering Business Worldwide

E SERIES NV UPS TECHNICAL SPECIFICATIONS - FOR HIGH AND LOW VOLTAGE MODELS

Model/Watts	E Series NV 400/240	E Series NV 600/360	E Series NV 800/480	E Series NV 1000/600	E Series NV 1400/840	E Series NV 2000/1200
Model Numbers (High Voltage)	ENV400H	ENV600H	ENV800H	ENV1000H	ENV1400H	ENV2000H
Model Numbers (Low Voltage)	ENV400L	ENV600L	ENV800L	ENV1000L	ENV1400L	ENV2000L
Technology	Line Interactive with Automatic Voltage Regulation					
Input / Output						
Input Voltage Window (HV)	170-280		160-280		166-280	
Input Voltage Window (LV)	89-145					
Output Voltage on Battery	120V (Low Voltage Models) / 230V (High Voltage Models)					
Frequency	50/60 Hz, auto-detection					
Data Line Protection	Input / Output jacks included for Telephone / Modem / Internet Line surge protection					
Output receptacles (High Volt)	4 ea, IEC style (1 output cable included)			6 ea, IEC style (1 output cable included)		
Output receptacles (Low Volt)	4 ea, NEMA 5-15 style			6 ea, NEMA 5-15 style		
Input Connection (High Volt Models)	Detachable 1.8M IEC input cable (cable included)					
Input Connection (Low Volt Models)	Attached 1.8M cable with NEMA 5-15P plug					Attachable cable with L5-20 input plug (cable included)

Battery

Load	E Series NV 400/240	E Series NV 600/360	E Series NV 800/480	E Series NV 1000/600	E Series NV 1400/840	E Series NV 2000/1200
100W	10	18	22	35	45	45
120W	7	14	17	-	-	-
200W	-	-	8	14	25	25
400W	-	-	-	6	10	10
600W	-	-	-	-	4	5
Start-On-Battery	Unit can be started without being connected to AC utility power – allows for portable power source					

User Interface

Visual	1 ON / OFF button, 1 indicator LED	1 ON / OFF button, six indicator LED's, including load level
Audible	Five audible alarms indicate operating modes	

Communications / management

Power Management Software	WINPOWER power management software, downloadable via internet
Connection Type	USB port, with included USB cable

Approvals

CE marking (High voltage models)

Dimensions and weights

Dimensions (high voltage models)	140 x 100 x 330 mm			205 x 145 x 385 mm		
Dimensions (low voltage models)	140 x 100 x 330 mm			205 x 145 x 385 mm	180 x 140 x 368 mm	
Weight (high voltage models)	5 kg	6 kg	6.5 kg	9.6 kg	10.5 kg	10.6 kg
Weight (low voltage models)	5 kg	6 kg	6.5 kg	9.6 kg	15 kg	16.1 kg

NV REAR PANEL

1. Output receptacles

2. AC Input

3. Modem Surge Protection

4. USB Communication Port

5. Circuit Breaker

6. Cooling Fan

High Voltage
400/600/800




Low Voltage
400/600/800




High Voltage
1000



Low Voltage
1000



High Voltage
1400/2000



Low Voltage
1400/2000



UNITED STATES
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794

www.eaton.com/eseries
www.eaton.com/nvups

CANADA
Ontario: 416.798.0112
Toll free: 1.800.461.9166

LATIN AMERICA
Argentina: 54.11.4124.4000
Brazil: 55.11.3616.8500
Caribbean: 1.949.452.9610
Mexico & Central America:
52.55.9000.5252
South Cone: 54.11.4343.6323

EUROPE/MIDDLE EAST/AFRICA
Denmark: 45.3686.7910
Finland: 358.94.52.661
France: 33.1.6012.7400
Germany: 49.0.7841.604.0
Italy: 39.02.66.04.05.40
Norway: 47.23.03.65.50
Portugal: 55.11.3616.8500
Sweden: 46.8.598.940.00
United Kingdom: 44.1753.608.700

ASIA PACIFIC
Australia: 61.2.9693.9366
New Zealand: 64.0.3.343.3314
China: 86.21.6361.5599
HK/Korea/Taiwan: 852.2745.6682
India: 91.11.4223.2300
Singapore/SEA: 65.6825.1668

Eaton is a trademark of Eaton Corporation.

© 2009 Eaton Corporation
All Rights Reserved
Printed in USA
NV01FXA
October 2009



Powering Business Worldwide